



28 years of innovation in lubricants, equipment, packaging

4	Director's word
6	Engine oils
12	Stages of oil production
20	White label oil production
24	Transmission oils
26	2T oils
28	Anti-sludge flush RESURS
30	Professional injector and combustion chamber cleaner for gasoline engines
34	Master Lubricant Valera
36	MC Blue and MC Rubin
38	Agro-lubricants
40	Polishes



Production facility in Maryino, St. Petersburg, Russia

THE SECRET OF SUCCESS ARE PEOPLE OF ACTION

Some people inherit from their parents, some see the panacea in investments and loans. We see it in people! I never cease to be amazed at the enormous creative potential that lies within almost everyone. Even that from kindergarten through high school it's being suppressed. We're like archaeologists digging down to the roots of creativity and motivate people to create.

If you are laboring and creating, you simply must use this word - BUSINESS.

THE HISTORY

When I came to start the company,

I was told "come and we'll help you close it in a month". We started with a small room of nine square meters where we had everything: a

And now, 28 years later, we are opening our third new facility to produce lubricants to replace the import products that are no longer available.



- 4000** recipes
- 700** products
- À ú » » 3» of production**
- 35** patents
- 2** racing teams

COMPETITIVENESS

Our presence in the tunnel boring materials market alone has forced powerful western companies to lower their prices.

PEOPLE

So how did we become successful? I'm sure many people are asking themselves this question. In 28 years, the company has not taken a single loan. Why should we? If properly organized, a business doesn't need loans. Conversely,

loans will only exacerbate the poor it means your product is losing out to the competition. Improve quality and lower prices, but this cannot be achieved without people's creativity. Develop, give people the opportunity to implement themselves in all areas and you will be successful. But it will take years.

Kuzmin Vasily , director

å
 Õ
 new line
 of PAO oil
 Modern

PAO
 +
 $\frac{\text{VHVI}}{\text{ESTER}} = \frac{\text{AN}}{\text{AN}}$
 Û ± h ÿ } N @
 å ? œ ô ± œ •

Mo
 L
 ú
 ú
 ¾
 »
 »
 ú
 t
 t
 8

High content of antifriction
 additives protect the engine
 from wear

SP

The oil meets the latest approval
 for modern vehicles that use fuel
 ^ç~•~^aÇ °~¤Áf

t
 ú
 •
 ô
 N
 N
 œ
 ±
 ú
 ž
 N
 ÿ
 ±
 }
 ?

Quadro



Truck synthetics: less carbon emissions — cleaner engine

code
9801

å ? œ ô ± œ ú • ú N & ú
ž Ô þ ñ ¯ ú / t > å > ‘ ú ¼ » # J ¿ »
Ô t ú ' t J ¿ # å ‘ ú ' > ú > ¿ # > Â

VHVI

Synthetic base increases oil life by 30% compared to semi-synthetics.

AN

Alkylated naphthalenes make the oil resistant to deposit formation and carbon deposits.



100,000
CARS HAVE
BEEN RUNNING
ON VMPAUTO
OIL

200vi*

Viscosity index, vs. 170 for
most analogs

APISN

Own additive package with
high molybdenum content

İİ
of mileage

Fracture resistant viscosity
index improver




Let's go!

Stages of oil production




Quality control takes place at all stages of engine oil production. The additive package, viscosity index improver solution and produced oil are fully analyzed

Elman Pendzhiev,
Elman Pendzhiev,
Technical Director




High viscosity index

Guarantee of durability.
VMPAUTO oils have a viscosity index 15% higher than that of their analogues.



Protection from oil change to change

Live tests at a taxi depot showed iron wear of only
5 parts per million after 10,000 km



“ VMPAUTO oils were tested on the vehicles of our
ÇsÛ~ é^^Çf ¼¼ Ö~~•¼^Á °sÁÁ^¼ Ç~^ Á^½
~sÖ~a' Ö°½ç^¼ ~a ¼~ç~¼¼Ç ì½~s^ •°a¼~Ç~°¼
rūtaxi

Anatoly Kurnikov
taxi service station

Internal combustion engine laboratory

In order to meet the tolerances of international organizations and car manufacturers, both laboratory and bench tests are required.

This is why we have established our own internal combustion engine laboratory, where we currently test **SL and SN** oils. In the near future we will launch a bench engine for testing of the most modern class of motor oils - **SP**.

Bench tests evaluate the following

Wear



Carbon deposits




Oil pressure, crankcase and bearing oil temperature



Acoustic indicators of internal combustion engine operation

dB



Up to 500 hours
of continuous motor
operation

Svyatoslav Alymov
research engineer

ВÃ»»úĐ'

That's the temperature of
brake discs while braking

At the limit

■ The AK Racing sports team took part in the REC endurance race, where the cars passed about 500 km at maximum rpm in 4 hours.



ВÂ»»úĐ'

The temperature in
the cabin of the car
during the 4-hour
race.

В¼Ã»»ú

Temperature in a thin
layer of oil



We will produce oil under your brand from 5 tons

We produce customized oil for you. Thanks to our state-of-the-art laboratory, we are able to control the properties of the future product. For example, to make an oil with a focus on low-temperature properties or for use in race cars.

Select base

Choose a viscosity index improver

Improve detergent oil properties

Balance proportion of antifriction additives

Katerina Zabrodkina
ekaterina.zabrodkina@vmpauto.com




' h t h • œ ú À » » ú œ N ?
of oil per month

Earn money on additional services

Everyone changes their oil. Competitors are growing like mushrooms, and it's hard to stand out.
 ìÇ Ö^ –sÕ^ s^ °ç^½ Ç–sÇ Ö~¤¤ sê½s•Ç •ÌÁÇ°©^½
 your service!


Engine decarbonization is simple:




Pour the solution in used oil



Run the engine for 20 minutes



Drain the oil
Change filter



Refill with fresh oil

from \$50 USD
for 35 min



code 9605

code 9412



Professional injector and combustion chamber cleaner for gasoline engines

¤~©~asÇ^Á •°aÇs©~asÇÁ„ ½^ÁÇ°½^Á º°áá¤^ Á°
 Removes carbon deposits from the combustion chamber
 Õì¤Ç s^„ °~ÁÇ°a ~°ê°©f P°¤Õ^Á Ç–^ °½°~¤^©
 fuel consumption

¾ » J Á » ú 8 ?
from \$30 USD

code 8505



Anti-sludge foam RESURS

Engine cleaning from high-temperature carbon deposits: carbon deposits, sludge. Removes deposits on valves, in Ç–^ ~^aÇsÇ^ ©s^~°¤„„ °a Ç–^ ~°ê°© °^ Ç–^ °~ÁÇ°
 area of compression rings

¾ » J Á » ú 8 ?
from \$30 USD

code 4305



RESURS NEXT

? h ? N @ ' N ? • ± ? œ } h œ ± ú

Restores damaged friction surfaces. Significantly reduces oil burn. Increases engine life. Equalizes compression. Result after 150 kilometers!

¾ » J Á » ú 8 ?
from \$30 USD

Durable gear oil

” Gear oil is changed much less frequently than engine oils. This means that it must be ready for a really long service life

Lasted longer than 90% of oils

The KRL test is performed to determine the reliability of the oil. The oil is destroyed by rotating a tapered bearing at 60 degrees for many hours.

Just imagine that for a Scania 1:0 tolerance the oil has to run for 20 hours, and for a Scania 2:0 it has to run for 100 hours. The enormous shear stresses involved should not destroy the oil any more than the standard tolerance.



' N ? Ü N } 8 Œ ú œ N ú Œ œ h corrosion test

Copper alloy based parts are found in the vehicle's transmission. For example, there are synchronizers in the manual gearbox. They are made of brass and Ç – ^ ° ~ ¨ Á – ° ì ¨ „ º ° Ç – s Œ ^ s Á Ç ½ ° a ' • ° ½ ½ ° Á them.



Â À # J Ä » Â À # J ¼ ¿ »
å • h ? h ú å ñ ~ ú ¼ å • h ? h ú å ñ ~ ú ½ : »

20 hours

¼ » 100 hours



VMPAUTO gear oil are within tolerances

Artem Grudtsin
Project X

Watch
the test



2T engine oils



code
9209



code
9231



code
9208



code
9230



No smoke, no fumes.



)
Read
DRIVE2

Stress test at 1/4 1/4 » » » ú } t 8


“The oil shows about zero wear when running in a chainsaw at 11,000 rpm for 8 hours straight!”



Nikolay Krylov
Engineer



Chainsaws



Trimmers



Lawnmowers



Motoblocks



Scooters



Motorcycles



RESURS Decarboil

deposits and do not return mobility to the oil
scraper rings, their task is a more complete
removal of residual waste oil from the engine.

code
9601

Used as a flushing
fluid works as
a decarbonizer

' & ± h ? ? á ú ± Ü Ü ± • œ Œ



Reduction of oil
burn



Compression
restoration

Over 10,000 reviews say the product works



Stages of engine decarbonization

Full
instructions



After 1
application




After 2
application



After 3
application



Clean
engine oil



Before

After 3 applications



Before

Before cleaning



After

After cleaning



code
9412



Before

Before cleaning



After

After cleaning

Professional injector and combustion chamber cleaner for gasoline engines



With the help of this product we defeated poor engine performance. Fuel consumption reduced from 43% to 3%. The product proved to be effective for all types of gasoline engines.

Andrei Toskin
Owner of Glissada-Drive from Yakutsk


Watch the video



Profitable service for your service

U-s a q A C ° C - ^ ^ C ~ O ^ a ^ A A ° ° C - ^ A ° ½ ° „ i • C „ ~ a i ^ • C ° ½ cleaning takes no more than one hour. A great way to s ê ½ • C • i A C ° © ^ ½ A C ° C - ^ A ^ ½ O ~ • ^ s a „ ^ s ½ a © ° a ~ Ü f

20 L



For non-disassembly cleaning via the fuel ramp



For injector cleaning machines



Protection: 1 bottle of 50 ml per 3-5 liters of oil

Restoration: 2 bottles per 3-5 liters of oil

Oil additive line

Protect and restore the engine with every oil change



4302

4305

4304



Fuel additive line

Just pour it into the fuel tank before refueling



9411

9403

9510

9515

9503

9303

code
1317




Blue.

High-temperature
grease

Base Oil Type:
Thickener Type:
Consistency Grade:
Welding load, not less than:
Base oil viscosity at 40°C:
Drop point:
Operating t° Range:
Grease color:

mineral
lithium complex soap
NLGI 2/3
2933
60 - 80 cSt
Ä qsn Þ
irn Þ fff Äovn Þ
blue



Base Oil Type:
Thickener Type:
Consistency Grade:
Welding load, not less than:
Base oil viscosity at 40°C:
Drop point:
Operating t° Range:
Grease color:

mineral
lithium-calcium soap
NLGI 2
2450
60 - 80 cSt
Äous Þ
irn Þ fff Äopn Þ
red

code
1413




Rubin.

Water resistant
grease

three greases for everything

Greases with extended change intervals for the maintenance of agricultural machinery.



Multipurpose

1 / J ¾

code
1154



Water-resistant

> Ô J ½

code
1160



High-temperature

‘ * J ½ ½ »

code
1166



Welding load

250 kgf

350 kgf

530 kgf

Base oil viscosity

180 sSt

600 sSt

220 sSt

Operating temperature

120 °C

120 °C

180 °C



DUBAI
CENTER

Polishing, not masking

Feedback from a specialist of
the Dubai Detailing Center, St.
Petersburg, Russia


“ VMPAUTO pastes proved to be worthy. They “cut” quickly and in our service they replaced German pastes in the painting section. I liked that they really polish, not mask. Á Ö^ ©^Ç °sÁÇ^Á,, Ç-^ ^Ç^•Ç °‘ Ö-~•- ¢sÁÇ^,, ìªÇ~¤ Ç-^ ‘~½ÁÇ wash.



Heavy cut

For removing severe damage to the
varnish layer.


ANALOGUES:
DETAIL DC,
MIRKA POLARSHINE 35,
MENZERNA: 1000 HEAVY
CUT COMPOUND



Medium cut

For scratch removal
and glossing

ANALOGUES:
q ý... s n r o u ! P U Z U I 3 Z
L 9 ... L P t t t ! p ! (9
CUTTING COMPOUND



Finely cut

To remove holograms,
to give a final gloss.

ANALOGUES:
L 9 ... L P t t t ! r
Z 3 U L ! (9 „
9 9 ? I L ! ? L 8 9 „
MENZERNA: 3800
P Z I L ! (9 (P & I 3 Z P

